

Titanium high performance wheelchairs

TiLite TR | TiLite ZR



permobil

TiLite TR

The best from every angle.

The sweeping curves of the titanium dual-tube frame combine striking design, enhanced performance, and optimal functionality. As our flagship rigid chair, the TR's efficiency and elegance move you to the pinnacle of performance.



TiLite ZR

Head turning style.

The ZR's titanium mono-tube frame means less truly is more. This minimalist aesthetic turns heads while the intentional frame design provides you the durability and vibration-dampening ride performance you expect from TiLite.




Tattoo options

- 1 Mosaic
- 2 Flower garden
- 3 Need for speed




Frame colours

High gloss paint




Metallic paint




Pearlescent paint




Matte paint




Candy paint



Matte textured paint




Natural Titanium



Component colours

Anodised



Specifications

TiLite TR

Frame features	Titanium Dual-Tube Rigid, TiFit, Limited adjustability	Centre of gravity adjustment	5"
Total chair width*	22"	Folding seat back	Adj. height 9.5" – 22" Adj. angle 80° – 101°
Seat width	12" – 20"	Fixed seat back	Fixed height 5" – 20" Fixed angle 80° – 101°
Front seat width (seat taper)	0", 1", 2"	Ergonomic seat	5" – 9"
Seat depth	12" – 20"	Transit options	-
Front seat height	15" – 21"	Transport weight*	4.2 kg
Rear seat height	12.5" – 20"	Weight limit	120 kg
Front frame angle	70°, 75°, 80°, 85°, or 90°	Warranty	Seven years on frame One year on TiLite components
Camber	0°, 2°, 4°, 6° or 8°		

TiLite ZR

Frame features	Titanium Mono-Tube Rigid, TiFit, Limited adjustability	Centre of gravity adjustment	2"
Total chair width*	23"	Folding seat back	Adj. height 9.5" – 22" Adj. angle 80° – 101°
Seat width	10" – 20"	Fixed seat back	Fixed height 8" – 20" Fixed angle 80° – 101°
Front seat width (seat taper)	0", 1.5"	Ergonomic seat	5" – 9"
Seat depth	10" – 20"	Transit options	Transport bracket
Front seat height	16" – 21"	Transport weight*	4.2 kg
Rear seat height	12.5" – 20"	Weight limit	120 kg Standard 136 kg Heavy duty
Front frame angle	70°, 75°, 80°, 85°, or 90°	Warranty	Seven years on frame One year on TiLite components
Camber	0°, 2°, 4°, 6° or 8°		

* Weights and widths based on 16" x 16" chair with 0° camber, minimum rear wheel spacing and all standard features. Rear wheels are not included in transport weight. For reference, a pair of standard 24" rear wheels weighs 3.3 kg.